

FIG. 1

09669583-091100




FIG. 2




FIG. 3





FIG. 4



**FIG. 5**

00160" 0956960




FIG. 6




FIG. 7




FIG. 8






FIG. 9

00160" 09565960




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17




FIG. 18

(a) IOBSI. IFO FILE 2130  
(IMAGE OBJECT SET INFORMATION RECODING REGION 142)

DATA SIZE WITH FIXED LENGTH	DATA SIZE WITH FIXED LENGTH	DATA SIZE WITH FIXED LENGTH	DATA SIZE WITH FIXED LENGTH
IOBSI MANAGEMENT INFO. 10	MANAGEMENT INFO. 1 CONCERNING IMG_01. IOB (COUNT INFO, OF IOB	MANAGEMENT INFO. 2 CONCERNING IMG_02. IOB (COUNT INFO, OF IOB	MANAGEMENT INFO. 9 CONCERNING IMG_999. IOB (COUNT INFO, OF IOB

(b)

(c) ATTRIBUTE INFO. 431  
ON STILL IMAGE (IOB)

REPRESENTATIVE IMAGE  
(OR JACKET IMAGE, ETC.)  
DESIGNATION STATE INFO. 432

\*N DENOTES A POSITIVE FIXED NUMBER

STILL IMAGE COMPRESSION METHOD AND COMPRESSION VERSION INFO. 441	STILL IMAGE RESOLUTION INFO. 442	FLAG FOR DISCRIMINATING RECORDED/UNRECORDED STATE OF IMG_01. IOB (OR DATA PRESENCE/ABSENCE FLAG) 41*	INFO. ON MUSIC NUMBER DESIGNATED AS REPRESENTATIVE IMAGE, ETC. 450	MUSIC NUMBER OR AOBI NUMBER/CI NUMBER/TKI NUMBER DESIGNATED AS FIRST REPRESENTATIVE IMAGE, ETC. 451	MUSIC NUMBER OR AOBI NUMBER/CI NUMBER/TKI NUMBER DESIGNATED AS N-TH REPRESENTATIVE IMAGE, ETC. 452
--	----------------------------------	---	--	--	---

← INFO. SIMILAR TO THOSE IS STORED IN MANAGEMENT  
INFO. 1 TO 9 OF IMG xx.IOB (xx=01 TO 999) →

FIG. 19




FIG. 20




FIG. 21

2




FIG. 23

START

GENERATE COMMON ENCRYPTION KEY (DECRYPTION KEY) BETWEEN MEDIUM AND DEVICE (BASED ON RANDOM NUMBER), AND STORE GENERATED KEY <ST12>

DURING RECORDING > PROCESSING FOR TRANSFERRING  
ENCRYPTED AUDIO/IMAGE INFORMATION TO MEDIUM  
DURING REPRODUCING > PROCESSING FOR TRANSFERRING  
ENCRYPTED AUDIO/IMAGE INFORMATION TO DEVICE <ST16>

## DECRYPTION PROCESSING FOR AUDIO/IMAGE INFORMATION USING COMMON ENCRYPTION KEY INFORMATION <ST18>

END

FIG. 24






FIG. 25




FIG.26

ST3000

USE DISPLAY MODE INFORMATION (51,52 IN FIG.20) IN IMAGE POINTER INFORMATION IPI OF AOB1 #1 OF MUSIC # $\alpha$  TO BE DISPLAYED FIRST IN COMBINED MUSIC (TRACK) # $\gamma$ , AS DISPLAY MODE INFORMATION OF COMBINED MUSIC # $\gamma$

ST3002

**NO**

**YES**

ST3008

**NO**

**YES**

DISPLAY SWITCHING TIMING OF STILL IMAGE IS SYNCHRONIZED WITH BOUNDARY BETWEEN AUDIO FRAMES OF MUSIC # $\gamma$  TO BE PLAYED BACK, DISPLAY OF STILL IMAGES IS SWITCHED AT GIVEN TIME INTERVALS USING TIMER, ETC.

## PLAY BACK AND DISPLAY STILL IMAGES

WHILE SWITCHING THEM BY DETERMINED DISPLAY METHOD (DISPLAY ORDER)  
AND/OR AT DETERMINED DISPLAY TIMING UPON PLAYBACK OF MUSIC #  $\gamma$

END

FIG. 27

[illegible]




FIG. 28